

NASTRO ISOLANTE ANTICONDENSA CINTA AISLANTE ANTICONDENSACIÓN CONDENSATION PREVENTION TAPE



Fornito in due versioni (gomma o polietilene). Reazione al fuoco Classe I. Temperatura di utilizzo: -15°C / +80°C.

Se suministra en dos versiones (goma y polietileno). Para aislamiento térmico. Reacción al fuego Clase I. Temperatura de funcionamiento -15°C / +80°C.

Supplied in two versions (rubber or polyethylene). Class I fire rating. Operating temperature: From -15°C / +80°C.

COD.			€
9898-500	50 x 3 mm x 10 m	40 pz	
9898-501	50 x 3 mm x 10 m	40 pz	
9898-503	50 x 3 mm x 10 m	40 pz	

Nastro in alluminio autoadesivo con collante forte. Classe I. Anticondensa. Temperatura di utilizzo -15°C/+80°C.

Cinta de aluminio autoadhesivo, con pegamento fuerte. Clase I. Anti-condensación. Temperatura de funcionamiento -15°C / +80°C.

Self-adhesive, condensation prevention aluminum tape with strong glue. Class I fire rating. Operating temperature: From -15°C / +80°C.

COD.			€
9898-400	50 x 0,3 mm x 50 m	24 pz	
9898-401	50 x 0,3 mm x 50 m	24 pz	

BENDA VINILICA RECUBRIMIENTO VINÍLICO | VINYL BAND

Rotoli in pvc elastico non adesivo. Rapidità e semplicità di montaggio, ottima resistenza agli acidi. Vengono impiegati per:

- Rivestimento esterno di protezione per tubi isolati;
- Protezione tubi interrati contro ossidazione e correnti vaganti;
- Protezione parti di manufatti da non trattare nei bagni galvanici (es: cromatura, zincatura ecc.);
- Si sconsiglia l'impiego su tubi esposti alla luce diretta del sole.

Rollos de PVC elástico no adhesivo. Rapidez y simplicidad de montaje, perfecta resistencia a los ácidos. Son utilizados para:

- Recubrimiento exterior para la protección de tubos aislados;
- Protección de tubos enterrados contra la oxidación y las corrientes dañinas del aire;
- Protección de partes de manufacturados a no tratar con baños de galvanización, (p. ej. partes cromadas, zincadas, etc.);
- Se desaconseja el uso para tubos expuestos a la luz solar directa.

Rolls of elastic non adhesive PVC. Quick and easy to apply, excellent resistance to acid. They are used for:

- External finishing and protection of insulated pipes;
- Protection for in ground pipes against oxidation and stray air flow;
- Protection of parts that cannot be treated with galvanizing baths, (i.e. chromium plating, galvanization, etc.);
- Not recommended for use on pipes exposed to direct sunlight.



COD.			€
9898-550-01	60m - h. 10 cm	30 pz	
9898-551-01	25m - h. 10 cm	70 pz	