

CARATTERISTICHE TECNICHE:

- Utilizzo su caldaie fino a 35 kW di potenza;
- Portata massima del fluido 3 l/h;
- Colonna minima necessaria 18 cm;
- Durata media del neutralizzante 8/12 mesi;
- Utilizzare neutralizzante specifico per condensa acida;
- Temperatura di esercizio Min/Max +4°C/+35°C.

CARACTERÍSTICAS TÉCNICAS:

- Uso en calderas de potencia hasta 35 kW;
- Caudal máximo del fluido 3 l / h;
- Cierre hidráulico mínimo requerido de 18 cm;
- Duración media de la neutralización de 8/12 meses;
- Usar neutralizador específico para neutralizar la condensación ácida;
- Temperatura de ejercicio Min/Máx +4°C/+35°C.

TECHNICAL FEATURES:


- Use on boilers up to 35 kW power;
- Maximum flow rate of the fluid 3 l / h;
- Minimum water seal required 18 cm;
- Average length of neutralizing 8/12 months;
- Use specific neutralizing for acidic condensation;
- Max/Min operating temperature +4°C/+35°C.

RICARICA RECARGA REFILL

COD.	€
AL-006A	



TUBO PVC TRASPARENTE TUBO TRANSPARENTE CLEAR PVC HOSE

COD.	Ø		€
9899-049-00	Ø 6x9 int	25 m	
9899-076-00	Ø 10x14 int	25 m	

Prezzo al metro
Precio al metro | Price per meter



SCHEMA DI MONTAGGIO ESQUEMA DE MONTAJE ASSEMBLY SCHEME

