

LC Drip Tray Range

The oil separator is designed to capture and retain light fluids, such as ester oils, within the containment system. For improved performance, it can be fitted with an optional high-efficiency heating block. In the event of a leak, light fluids are efficiently separated and securely retained in full compliance with regulations. Rainwater is directed through the separator, creating a natural barrier that prevents oil from escaping and ensures safe containment.

Safety First
AuRü

KEY FEATURES:

- Automatic activation below 5°C with water detection
- Integrated thermostat-controlled heating cable
- LED status indicator on PCB
- Included thermostat
- Customisable operating modes via 4-pole DIP switch
- Switches on at +3°C
- Turns off at +8°C
- Includes a leaf guard and drain nozzle
- Corrosion resistant

KIT INCLUDES:

- Surface heating unit
- Stainless steel mounting plate
- Pre wired electrical connection

Part No.	Model	Dimensions (H×W×L)	Retention capacity
100-00-2020	AuRü-LC-2	80 x 400 x 950 mm	approx. 1.5 litres
100-00-2030	AuRü-LC-3	80 x 500 x 1200 mm	approx. 2.4 litres
100-00-2050	AuRü-LC-5	80 x 1000 x 1200 mm	approx. 4.8 litres
100-00-2060	AuRü-LC-6	80 x 1200 x 1200 mm	approx. 5.8 litres
100-00-2070	AuRü-LC-7	80 x 1200 x 1500 mm	approx. 7.2 litres
100-00-2080	AuRü-LC-8	80 x 1200 x 1750 mm	approx. 8.4 litres